Ricoh Aficio Color 5560V

Color Digital Imaging System
The New Benchmark for High-Speed
Color Communications





Ricoh Aficio Color 5560V



MultifunctionalFlexibleManageable

Color with Quality, Speed and the Ultimate Simplicity

The Ricoh Aficio Color 5560V is designed for productivity, usability and superior image quality, with an array of color calibration and registration technologies to ensure sharp, consistent results.

- Speeds of up to 55 ppm full color and 60 ppm black & white combine with true 600 dpi scanning and printing so that every page always looks its best.
- Automatic Color Selection (ACS) determines which pages to reproduce in color or black & white, even within mixed sets.
- The Color Usage Restriction function assures you're only paying for the color you use by controlling the color usage activity of others.
- Oil-less toner formula delivers a rich color gamut and hardcopies with just a touch of gloss.
- Replacing toner is as simple as dropping the toner bag into the respective hopper.
- User-adjustable paper drawers automatically detect the loaded paper size, making additional programming unnecessary.

Multifunction Means More than Copying and Printing

If information sharing and archiving are as critical to your business as hardcopy document production, utilize the Ricoh Aficio Color 5560V's full-color scanning.

- TWAIN scanning lets you digitize hardcopy originals for incorporation into new documents.
- The 100-Sheet Automatic Reversing Document Feeder quickly captures one- or two-sided originals at speeds up to 60 ipm (images per minute) for monochrome documents and 45 ipm for color pages.
- The scanner detects the size of each original, while Automatic Paper Selection (APS) chooses the proper copy paper size automatically.
- Control the level of detail, file size and file format so users can open, view and/or print documents exactly as they were created.

Diverse Document Management and Distribution Capabilities

The Ricoh Aficio Color 5560V comes complete with a full complement of standard utilities for storing, organizing, retrieving and distributing your documents and data.


- Versatile color Scan-to functions allow for efficient document storage and distribution to hundreds of e-mail addresses or networked File/Folder/FTP destinations in a single operation.
- Document Server function scans, stores and organizes up to 3,000 documents with the power of 1,384MB RAM and a 4 x 80GB Hard Disk Drive array.
- DeskTopBinder combines and publishes files from various applications as a single, cohesive document.



The Ricoh Aficio Color 5560V control panel features an intuitive design with clearly labeled hard keys and easy-to-understand icons. This same ease of use is available through the Ricoh RPCS (Refined Print Command Stream) print driver.



Choose from several high-capacity Finishers with multi-position stapling and/or hole punching, and even produce saddle-stitched, folded booklets in-house.



Access and manage your document production system with just a few clicks of the mouse to optimize your printing productivity with Ricoh RPCS (Refined Print Command Stream).

CopyPrintScanManage

Streamlined Design and Enhanced Control Improve Productivity

The easier office equipment is to use and control, the more productive your employees will be. That's why Ricoh has designed the Aficio Color 5560V to be easy to operate, easy to manage, and easy to get the desired results, every time.

- Enormous 7,400-sheet maximum paper supply means less interruptions and less maintenance.
- Full-format capabilities let you output full-bleed spreads of facing pages on 12" x 18".
- Several high-capacity Finishers offer multi-position stapling and/or hole punching, and even let you produce duplexed saddle-stitched booklets.
- Tab Accessory produces color tabs to separate sections for that professionally published look in binders, handbooks and manuals.
- LDAP Authentication ensures only authorized users with active usernames and passwords can access the system, while advanced data encryption ensure security and integrity.
- HDD DataOverwriteSecurity System (DOSS) automatically overwrites information using methods that conform to National Security Agency (NSA) standards.
- Web Image Monitor tracks system use and status in real-time letting you check or change printer settings, view job histories and device status, monitor toner and paper levels, reset print jobs or reboot the printer—all without ever leaving your desk.
- Control panel features an intuitive design with clearly labeled hard keys and easy-to-understand icons.

Versatile Networking Support for Any Environment

The Ricoh Aficio Color 5560V is compatible with all of the most popular computing environments, making it a great solution for the wide range of jobs produced by general business users every day.

- The 10/100BaseTX Ethernet interface allows every user to share the power of high-speed color printing, while the USB 2.0 port enables peer-to-peer device access and control.
- Optional IEEE 802.11b or Bluetooth wireless interface meets your special connectivity needs.
- Wireless connectivity simplifies printing for visitors and gives you the benefits of networked printing without a LAN connection.
- Auto Switching technology means a seamless adjustment to data streams generated by Windows®, Macintosh® or UNIX clients in mixed-network environments.
- Standard support for the Ricoh RPCS and PCL 5c/6 page description languages and drivers, with optional genuine Adobe® PostScript® 3™.



Your Environmental Partner





Ricoh continues its long-standing commitment to developing office solutions with environmentally friendly and superior energy- and supply-saving features, without compromising productivity, including:

- Quick Start-Up (QSU) Technology
- Power-Saving Sleep Mode
- Duplex and Combine Copy Modes
- Toner Recycling
- Low Noise Levels
- Minimal Ozone Emissions
- Restriction of Hazardous Substances (RoHS) Compliant

FastSimpleProductive





Ricoh Aficio Color 5560V

System Specifications

General Specifications

Printing Process 4-drum Electrostatic Transfer System with Internal Transfer Belt and Dry Two-component Development

Output Speed Black & White: 60 ppm Full-Color: 55 ppm 1 to 999

Multiple Copies Warm-up Time 300 seconds First Copy Time Black & White: 6.5 seconds Full-Color: 7.5 seconds

Copy Resolution 600 x 600 dpi Books/Sheets/3D Objects Original Type Output Size 5.5" x 8.5" to 11" x 17 Full bleed output on 12" x 18"

Maximum Image 11.69" x 18" Area

Standard Paper Capacity Optional Paper

Supply Paper Sizes/Weights

Paper Types

(max. capacity: 7,400 sheets) Standard Tray 1: 8.5" x 11"/ 14 - 34 lb. Bond (52.3 - 127.9 g/m²) Standard Trays 2 & 3: Up to 12" x 18"/ 14 - 34 lb. Bond (52.3 - 127.9 a/m²) 100-Sheet Bypass: Up to 12" x 18"/ 14 lb. Bond- 140 lb. Index (52.3 -127.9 g/m²)

4.000-Sheet LCT

4,000-Sheet LCT: 8.5" x 11"/ 14 – 34 lb. Bond (52.3 – 127.9 g/m²) Plain paper, Recycled paper, Laser qualified transparencies

1,100 x 2 + 550 x 2 + 100 Bypass

Duplexing Standard **Output Tray Capacity** 500 sheets

25% - 400% in 1% increments Zoom **Reduction Ratios** 93%, 85%, 78%, 73%, 65%, 50%, 25% **Enlargement Ratios** 121%, 129%, 155%, 200%, 400% Document Server stores up to 3,000 Page Memory (LTR) documents; Maximum pages per

document: 2,000 pages **Power Source** 120V/20A, 60Hz Maximum Power Less than 1.920W

Consumption Dimensions (WxDxH) 29.5" x 33.5" x 41.3" (750 x 850 x 1050 mm) excludes standard ARDF 656.9 lbs. (298 kg) includes standard ARDF) Weight

Printer Controller Specifications (Standard)

Intel Celeron LV @ 733 MHz Memory 1,384MB RAM Std./Max. (Shared) 4 x 80GB HDD = 320GB HDD (Shared) RPCS, PCL 5c/PCL 6

Page Description Adobe®PostScript®3™/PDF Direct Print Languages

(optional) PCL Fonts PCL: 45 fonts

PostScript Fonts 136 Adobe PostScript Type 1 fonts (optional)

Print Resolution 600 x 600 dpi

Standard Interfaces 10BaseT/100BaseTX Ethernet, USB 2.0 IEEE 1284/ECP Type A, IEEE 1394 Type Optional Interfaces

B, IEEE 802.11b Wireless LAN Unit Type H, Bluetooth Type 3245 (Choose one) Network Protocol TCP/IP, IPX/SPX; SMB (NetBIOS over TCP/IP)

Apple Talk (Auto Switching) RPCS, PCL 5c/6 and PS: Drivers

Windows 95/98SE/NT4.0/2000/Me/XP/ Server 2003 Netware 3.12, 3.2, 4.1,

4.11, 5.0, 5.1, 6

PS: Mac OS 8.6 – 9.2x, OS X 10.1 or later UNIX; Sun Solaris, HP–UX, SCO OpenServer, RedHat Linux, IBM AIX SmartDeviceMonitor for Administrator

Utilities and Client. Web SmartDeviceMonitor. Web Image Monitor, DeskTopBinder Lite

Security Features

DataOverwriteSecurity System (DOSS) Type C (Optional): Security feature that overwrites latent data on the system's hard drive after copy, scan and print jobs. Other Security Features: Locked (Secure) Print, SSL print, SNMP v3 support. Windows Authentication

Scanner Specifications

Scanning Speed

Scan-to Modes

Supported

Scanning Resolution Full-color mode: From 100 – 600 dpi (1,200 dpi TWAIN)

Monochrome mode From 100 - 600 dpi Default Setting: 200 dpi Black & White: 60 spm

Full-Color: 45 spm Maximum: 11.69" x 17" Scan Area 5.5" x 8.5" to 11" x 17" Original Size **Protocol Supported** Network: TCP/IP;

Scan-to-Email: SMTP; Scan-to-Folder: SMP, FTP

Black & White: TIFF (Single/Multi File Format Page), PDF (Single/Multi Page)

Grayscale: JPEG (Single Page) Full-Color: PDF (Single/Multi Page) Scan-to-Email (with LDAP support), Scan-to-Folder FTP/SMB, Network TWAIN scanning

Hardware Accessories

Automatic Reversing Document Feeder (Standard)

Original Size 5.5" x 8.5" to 11" x 17" Simplex: 11 lb. - 34 lb. Bond **Original Weight** (40 - 128 g/m²)

Duplex: 14 lb. – 34 lb. Bond (52 - 128 g/m²) 100 Sheets

Original Stack Capacity

Large Capacity Tray (Optional)*

Paper Capacity 4,000 sheets (Letter) 2,500 sheets (Legal)** 8.5" x 11", 8.5" x 14" ** Paper Sizes

Paper Weights 14 lb. - 34 lb. Bond (52 - 128 g/m²) *Requires LCT Adapter

**Requires Legal size conversion kit

9-Bin Mailbox (Optional)* Number of Bins Stack Capacity per Bin 100 sheets

Acceptable Paper Size 5.5" x 8.5" to 11" x 17"

Acceptable Paper 14 lb. - 34 lb. Bond (52 - 128 g/m²)

Weight

*Cannot be used with SR842 Finisher or Interposer

SR842 3,000-Sheet Finisher w/100-Sheet Stapling (Optional)*

Number of Trays Paper Sizes 5.5" x 8.5" to 11" x 17"

. Acceptable Paper 14 lb. Bond - 140 lb. Index (52 – 128 g/m²) Proof Tray: 500 sheets (8.5" x 11" or smaller) Weights Stacking Capacity

250 sheets (8.5" x 14" or larger) Shift Tray: 3,000 sheets (8.5" x 11" or smaller)

1,500 sheets (8.5" x 14" or larger) Up to 100 pages per set

(8.5" x 11" or smaller) Up to 50 sheets per set (8.5" x 14" or larger) 8.5" x 11" to 11" x 17"

Staple Paper Size Staple Paper Weight 17 lb. - 20 lb. Bond (64 - 84 g/m²) **Staple Positions** Top, Bottom, 2 Staple, Top Slant Finisher Accessories Hole Punch Unit, Jogger Option *Requires Finisher Adapter

SR970 3,000-Sheet Finisher w/50-Sheet Stapling

(Optional) Number of Trays

Staple Capacity

Acceptable Paper 5.5" x 8.5" to 12" x 18"

Acceptable Paper Weight Stacking Capacity

(52 - 256 g/m²) (32 – 236 g/llf) Proof Tray: 250 sheets (8.5" x 11" or smaller) 50 sheets (8.5" x 14" or larger) Shift Tray: 3,000 sheets (8.5" x 11" or smaller) 1,500 sheets (8.5" x 14" or larger)

14 lb. Bond - 140 lb. Index

Staple Capacity Up to 50 pages per set

(8.5" x 11" or smaller) Up to 30 sheets per set (8.5" x 14" or larger) 8.5" x 11" to 11" x 17" 17 lb. - 28 lb. Bond (64 - 90 g/m²)

Staple Paper Weight Staple Positions Top, Bottom, 2 Staple, Top Slant Finisher Accessories Hole Punch Unit, Jogger Option SR4000 2,000-Sheet Finisher w/Saddle Stitch Stapling

(Optional)
Number of Trays

Staple Paper Size

Paper Sizes 5.5" x 8.5" to 12" x 18" Acceptable Paper 14 lb. Bond - 140 lb. Index Weights (52 - 256 g/m²) Proof Tray: 250 sheets (8.5" x 11" or smaller) Stacking Capacity

50 sheets (8.5" x 14" or larger) Shift Tray: 2,000 sheets (8.5" x 11" or smaller)

1,000 sheets (8.5" x 14" or larger) Staple Capacity Up to 50 pages per set

(8.5" x 11" or smaller) Up to 30 sheets per set (8.5" x 14" or larger) Saddle Stitch: Up to 15 sheets 8.5" x 11" to 12" x 18"

Staple Paper Size 17 lb. - 28 lb. Bond (64 - 90 a/m²) Staple Paper Weight **Staple Positions** Top, Bottom, 2 Staples, Top Slant, Saddle Stitch

8.5" x 11", 8.5" x 14", 11" x 17", 12" x 18" SEF Saddle Stitch Paper

Size Finisher Accessories Hole Punch Unit, Jogger Option

Cover Interposer Tray (Optional)* Stack Capacity 200 sheets

5.5" x 8.5" to 11" x 17" Paper Sizes 17 lb. Bond - 110 lb. Index Acceptable Paper Weight (64 - 216 g/m²)

*Cannot be used with SR842 or 9-bin mailbox

GBC StreamPunch III (Optional)* 8.5" x 11" IFF Paper Size

20 lb. Bond – 110 lb. Index (216 g/m²) CombBind®, Twin Loop wire (2:1 or Paper Weight Die Sets

3:1), ColorCoil®, VeloBind®, Three-Ring,

ProClick®

BK5010 Production Booklet Maker (Optional)*

Paper Size Paper Weight 16 lb. Bond - 110 lb. Index (216 g/m²)

*Requires SR842 Finisher

Other Optional Accessories

Copy Tray*

Tab Sheet Unit 11" x 17" Tandem Tray Converter

Legal Tray for LCT

Adobe PostScript 3 Unit Type 3260 Copy Connector Type 3260 File Format Converter Type B

*If one of the finishers is not selected, the Copy Tray is required

Black Toner Cartridge 36K output/cartridge (LTR 5% coverage) Cyan Toner Cartridge 18K output/cartridge (LTR 5% coverage) 18K output/cartridge (LTR 5% coverage) Magenta Toner Cartridge

Yellow Toner Cartridge 18K output/cartridge (LTR 5% coverage)

Staple for 100-Sheet 5,000 per cartridge Stapler

Staple for 50-Sheet 5,000 per cartridge Stapler Staple for Saddle 2,000 per cartridge

Stitch Stapler

Bluetooth











@Remote





